

**ORDERING METHOD**

TYPE	Drive	Rated torque	Rotation angle	Angular velocity
		Nm	°	rpm
ESW-25-00	asynchronous 3-phase motor, type Skg71-8B 0.12kW; 690rpm, 230/400V, 50Hz	250	90°	0.24

CODE1	PROTECTION TYPE
-00	standard version

CODE2	CLIMATIC VERSION
-01	version N2, acc. to PN-68/H-04650 (for temperate climate zone, outdoor under roof operation on land)

CODE3	EQUIPMENT
-1	without angular encoder*
-2	angular encoder type EPO-02; 4...20mA digital un-contacting (2-wire)*
-3	angular encoder type EPO-03; 4...20mA digital un-contacting (2-wire)*
-7	angular encoder type EPO-01; 4...20mA analog potentiometric (2-wire)

CODE4	TRAVEL ADJUSTMENT
-2	double travel-switches

CODE5	CONNECTORS
-01	with crank
-02	without crank, with clutch - acc. to drg. no. 1
-03	with crank and ball-and-socket joints
-04	with crank, ball-and-socket joints and shock absorber

**ESW-25-00 - 00 - 01 - 2 - 2 - 01** EXAMPLE OF ACTUATOR TYPE DENOTATION

\*- if client doesn't determine output connector in the order, manufacturer will make actuator with 42-pin HARTING connector (housing of plug has 2 glands: 1xPG21 and 1xPG 13,5); AMPHENOL connector should be mentioned in order.

**Meaning symbols of ESW-25-00-00-01-2-2-01:**

- |            |   |
|------------|---|
| ESW-25-00- | - electric part-turn actuator of rated torque 250Nm, angular positioning speed - 0.25 rpm<br>and rated rotation angle 90° |
| -00        | - standard version  |
| -01        | - temperate climate version   |
| -2         | - with angular encoder type EPO-02; 4...20mA digital un-contacting (2-wire)   |
| -2         | - with double travel switches   |
| -01        | - with crank  |